

FSM-100M

Specialty fibre fusion splicer

FEATURES

- Splices 80-500µm cladding fibre
- Patented split V-groove and electrode systems create flexibility within the Plasma Zone.
- Fibre profile learning – the splicer learns the fibre profile to shorten splice time.



TELECOMMUNICATIONS FIBRES	SMF(ITU-T G652), NZDSF(ITU-T G655), MMF(ITU-T G651), EDF, DCF and other specialty fibres
LARGE DIAMETER FIBRE	Conventional silica LDF
FIBRE CLAD DIAMETER	φ60µm to 500µm
FIBRE COATING DIAMETER	φ100µm to 2000µm
FIBRE COUNT	Single
CLEAVE LENGTH	Glass clamp: 8mm to 10mm (standard 9mm); Coating clamp: 3mm to 5mm (standard 4mm)
TYPICAL SPLICE LOSS	0.03dB [SMF], 0.05dB [NZDSF/LDF], 0.02db [MMF]
SPLICE TIME	15 sec. [SMF/MMF], 25 sec. [NZDSF/LDF]
RETURN LOSS	>> 60dB
SPLICE TIME	15 sec. [SMF/MMF], 25 sec. [NZDSF/LDF]
TUBE HEAT TIME	30 sec. [FP-03 40mm], 35 sec. [FP-03 60mm], 55 sec. [FPS01 series (micro sleeve)]
FIBRE CLAMP	It changes automatically according to cladding diameter and coating diameter
SWEEP RANGE	±5mm (arc centre is 0mm)
ELECTRODE LIFE	2500 arc discharges for SMF (ITU-T G.652) splicing with 1mm electrode gap
ELECTRODE GAP	1mm to 3mm (adjustable)
ELECTRODE OFFSET	-0.3mm to +0.1mm (adjustable)
PROOF TEST	1.96N to 2.45N
MAGNIFICATION	58 to 300 (changeable)
AUTO-START FUNCTION	Yes
SPLICE MODES	Total 300 modes including Standard, Manual, Power Meter and Attenuation modes)
TUBE HEATING MODES	100
SPLICE RESULT STORAGE	Last 2000 results stored in internal memory
LANGUAGE	English, Japanese, Chinese
FIBRE LEARNING FUNCTION	Yes
PC CONNECTION	Yes (for software upgrade, displaying image data, viewing splice results and conditions, and PC control)
DISPLAY	Dual 4.1-inch colour LCD monitors
DIMENSIONS	311mm [W] x 232mm [D] x 160mm [H] excluding rubber feet
WEIGHT	7.5kg
POWER SUPPLY	External AC adapter: ADC-15; Input: AC100 to 240V (50 to 60Hz) (max.100W AC)
OPERATING CONDITIONS	0 to 95% RH and 0°C to 40°C
STORAGE CONDITIONS	0 to 95% RH and -40°C to 80°C
TERMINALS	DC19V 4.5A power supply, USB 2.0 (Mini-B type) for PC communication, IEEE-488 24 pin for power monitor feedback alignment, two six-pin Mini-DIN connectors for external equipment (HJS-02)